

PERISTALTIC PUMPS

MAINTENANCE MADE EASY

CREATED FOR THE SWIMMING POOL, SPA AND HOT TUB PROFESSIONAL.



hard wired configuration



three-roller operation

- RC-25/53 SC - 12 GPD
- RC-103 SC - 32 GPD
- RC-503 SC - 72 GPD



two-roller operation (1) GPD pump only

RC-252 SC - 1 GPD



521160

3/8" Hose Barb x 3/8" Hose Barb



521170

3/8" Hose Barb x 1/4" MNPT

CHECK VALVES



527158



520113

INJECTORS

All **ROLA-CHEM** pumps come with a 1/2" brass injection fitting and a 1/4" plastic injection adapter.

Our **Pro Series** Peristaltic pumps deliver professional quality as well as features that make operation and maintenance simple. The quality is easily seen in the **Pro Series'** durable plastic construction that is resistant to swimming pool, spa and hot tub chemicals.

Some other features you will enjoy include:

- A quick release cover for fast tubing access
- Electronic controls for extended motor life
- A three-way switch control for priming, shock feeding or stopping feed without disturbing your feed-rate setting
- Self-priming pump
- Includes Clear Tygon (Chlorine) and Black Norprene (Acid or Chlorine) Tubes
- 30 psi rating
- 18-ft. suction lift
- Pumps operate on 9-minute cycles
- Available in 120V or 240V corded or permanent wire
- Maximum amps - 2.5
- **One-year limited warranty (tubing not included)**

ROLA-CHEM PRO SERIES OUTPUT RATES

MODEL	MINIMUM FEED RATE/24HR	MAXIMUM FEED RATE/24HR	RECOMMENDED POOL/SPA CHLORINE TO FEED RATE
*RC252SC	.01 GPD	1.0 GPD	UP TO 500 GALLONS
RC25/53SC	.10 GPD	12 GPD	500 - 65,000 GALLONS
RC103SC	.30 GPD	32 GPD	500 - 150,000 GALLONS
RC503SC	.80 GPD	72 GPD	150,000 - 500,000 GALLONS

ROLA-CHEM PRO SERIES ESTIMATED MAXIMUM GALLONS PER DAY

SETTINGS	ON	OFF	RC252	RC25/53	RC103	RC503
LO	4 SEC.	8 MIN. 56 SEC.	0.01	0.10	0.30	0.80
2	1.5 MIN.	7.5 MIN.	0.10	1.20	3.20	7.20
3	3 MIN.	6 MIN.	0.30	3.60	9.60	22.00
4	4.5 MIN.	4.5 MIN.	0.50	6.00	16.00	36.00
5	6 MIN.	3 MIN.	0.70	8.40	22.00	50.00
6	7.5 MIN.	1.5 MIN.	0.90	11.00	29.00	65.00
HI	8 MIN. 56 SEC.	4 SEC.	1.00	12.00	32.00	72.00
OUNCES PER MINUTE AT FULL ON			0.178	2.13	5.70	12.80

ROLA-CHEM PUMPS

ARE NSF® c UL® US LISTED.